
Epson AcuLaser M2400DN

DATASHEET



Designed for small-to-medium workgroups, this efficient printer gets the job done fast with a first-page-out time of 7 seconds and a print speed of up to 35 pages per minute. There's no compromise on quality with a professional print resolution of 1200 x 1200dpi.

Flexible and expandable: The AcuLaser M2400DN has the flexibility to perfectly match the needs of your workgroups, with expandable RAM from 64MB up to 320MB. Paper handling is adjustable too, with automatic double-sided printing and a choice of one or two optional additional paper trays to increase capacity to 800 sheets.

Easy compatibility: Seamlessly integrating into most IT environments, the AcuLaser M2400DN supports PCL5e, PCL6, standard ESC/Page, FX, ESCP2, 1239X, Genuine PostScript 3™ and PDF 1.3. It also features Ethernet connectivity for easy sharing across workgroups.

Lower costs and environmental impact: Your company's cost per page is optimised with a choice of standard and high-capacity toner cartridges. The printer's ENERGY STAR qualified power efficiency and Epson's toner cartridge return programme further reduce bills and minimise environmental impact.

KEY FEATURES

- Fast printing - Up to 35ppm
- High-quality prints - 1200 x 1200dpi print resolution
- Network-ready - Ethernet connectivity
- Save paper - Automatic double-sided printing
- Flexible capacity - Expandable RAM and paper capacity

PRODUCT SPECIFICATIONS

TECHNOLOGY	
Printing Resolution	1,200 dpi
PRINT	
First Page Out	Monochrome 7 Seconds
Max Duty cycle	50,000 Pages per month
CONNECTIVITY	
Interfaces	USB 2.0 Type B, Ethernet interface (100 Base-TX / 10 Base-T)
Network Printing Protocols	LPR, FTP, IPP, Port 2501, Port 9100, WSD, Net BIOS over TCP/IP, Net BIOS over NetBEUI, AppleTalk
Network Management Protocols	SNMP, HTTP, DHCP, BOOTP, APIPA, DDNS, mDNS, SNTP, SSDP, SLP, WSD, LLTD, Ping
PAPER / MEDIA HANDLING	
Paper Formats	A4, A5, A6, B5, C5 (Envelope), C6 (Envelope), DL (Envelope), No. 10 (Envelope), LT, HLT, LGL, EXE, User defined
Duplex	Yes
Output Tray Capacity	250 Sheets
Paper Tray Capacity	300 Sheets Standard, 800 Sheets maximum
Number of Paper Trays	2 Trays
GENERAL	
Product dimensions	378 x 390 x 255 mm (Width x Depth x Height)
Product weight	11.5 kg
Temperature	Operation 10° C - 32.5° C
Humidity	Operation 15% - 80%, Storage 15% - 80%
OTHER FEATURES	
Memory	64 MB included, 320 MB maximum
Emulations	PCL5e, PCL6, ESC/P2, ESC/Page, IBM 2390, PostScript 3
OTHER	
Warranty	12 months On site service

WHAT'S IN THE BOX

- Main unit
- Setup guide
- User manual (CD)
- Driver and utilities (CD)
- Software (CD)
- Warranty document
- Power cable

LOGISTICS INFORMATION

- SKU
C11CB47101BX
- Barcode
8715946478395
- Dimensions Single Carton
520 x 515 x 390 mm
- Carton Weight
14.36 Kg
- Pallet Size Euro
2 Units (5 x 10)
- Pallet Size Block
2 Units (5 x 10)

For more information please contact:

Telephone: 0871 222 6702 (UK)+
01 436 7742 (Republic of Ireland)
E-mail: enquiries@epson.co.uk
Chat: etalk.epson-europe.com
Fax: 0871 222 6740

Web: www.epson.co.uk
www.epson.ie

+ Calls cost 10p per minute plus network extras.

Trademarks and registered trademarks are the property of Seiko Epson Corporation or their respective owners.
Product information is subject to change without prior notice.

EPSON®